

Safety Data Sheet

WALLTITE® XL RESIN

Revision date : 2019/02/08
Version: 3.0

Page: 1/10
(30676744/SDS_GEN_CA/EN)

1. Identification

Product identifier used on the label

WALLTITE® XL RESIN

Recommended use of the chemical and restriction on use

Recommended use*: polyurethane component; industrial chemicals
Suitable for use in industrial sector: Polymers industry; chemical industry

* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Details of the supplier of the safety data sheet

Company:
BASF Canada Inc.
100 Milverton Drive
Mississauga, ON L5R 4H1, CANADA

Telephone: +1 289 360-1300

Emergency telephone number

CHEMTREC: 1-800-424-9300
BASF HOTLINE: (800) 454-COPE (2673)

Other means of identification

Chemical family: Preparation based on: polyol, catalyst, additives
Synonyms: Urethane System Resin Component

2. Hazards Identification

According to Hazardous Products Regulations (HPR) (SOR/2015-17)

Classification of the product

Skin Sens.	1	Skin sensitization
STOT RE	2 (oral)	Specific target organ toxicity — repeated exposure
Aquatic Acute	3	Hazardous to the aquatic environment - acute
Carc.	2	Carcinogenicity

Label elements

Safety Data Sheet

WALLTITE® XL RESIN

Revision date : 2019/02/08
Version: 3.0

Page: 2/10
(30676744/SDS_GEN_CA/EN)

Pictogram:



Signal Word:
Warning

Hazard Statement:

H317 May cause an allergic skin reaction.
H351 Suspected of causing cancer.
H373 May cause damage to organs (Kidney) through prolonged or repeated exposure (oral).
H402 Harmful to aquatic life.

Precautionary Statements (Prevention):

P280 Wear protective gloves/protective clothing/eye protection/face protection.
P201 Obtain special instructions before use.
P260 Do not breathe dust/gas/mist/vapours.
P202 Do not handle until all safety precautions have been read and understood.
P273 Avoid release to the environment.
P272 Contaminated work clothing should not be allowed out of the workplace.

Precautionary Statements (Response):

P314 Get medical advice/attention if you feel unwell.
P308 + P311 IF exposed or concerned: Call a POISON CENTER or doctor/physician.
P303 + P352 IF ON SKIN (or hair): Wash with plenty of soap and water.
P362 + P364 Take off contaminated clothing and wash it before reuse.

Precautionary Statements (Storage):

P405 Store locked up.

Precautionary Statements (Disposal):

P501 Dispose of contents/container in accordance with local regulations.

Hazards not otherwise classified

No specific dangers known, if the regulations/notes for storage and handling are considered.

3. Composition / Information on Ingredients

According to Hazardous Products Regulations (HPR) (SOR/2015-17)

<u>CAS Number</u>	<u>Weight %</u>	<u>Chemical name</u>
		HMIRA Registry number 11762, Date of Filing: August 22, 2017
Trade Secret	>= 25.0 - < 50.0%	Aminoalkylalkanolamine polymer with alkoxide
Trade Secret	>= 15.0 - < 20.0%	Alkyl halide Phosphate
Trade Secret	>= 5.0 - < 7.0%	Halogenated Aromatic Carboxylic acid
Trade Secret	>= 0.3 - < 3.0%	Hydroxyalkyl ether
Trade Secret	>= 0.1 - < 1.0%	Dialkylhetero monocycle
Trade Secret	>= 0.1 - < 1.0%	Bis(dialkylaminocarbomonocyclic)alkylene-carbomonocyclic, ammonium salt

Safety Data Sheet

WALLTITE® XL RESIN

Revision date : 2019/02/08
Version: 3.0

Page: 3/10
(30676744/SDS_GEN_CA/EN)

4. First-Aid Measures

Description of first aid measures

General advice:

Remove contaminated clothing.

If inhaled:

Keep patient calm, remove to fresh air, seek medical attention.

If on skin:

Wash affected areas with water for at least 15 minutes. If irritation develops, seek medical attention.

If in eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open.

If swallowed:

Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.

Most important symptoms and effects, both acute and delayed

Symptoms: The most important known symptoms and effects are described in section 2 and/or in section 11.

Information on: Hydroxyalkyl ether

Symptoms: Overexposure may cause: vomiting, coma, abdominal cramps, lethargy, nausea, diarrhea, headache

Indication of any immediate medical attention and special treatment needed

Note to physician

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media:
water spray, dry powder, carbon dioxide, foam

Special hazards arising from the substance or mixture

Hazards during fire-fighting:
No particular hazards known.

Advice for fire-fighters

Protective equipment for fire-fighting:
Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

Further information:

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

Safety Data Sheet

WALLTITE® XL RESIN

Revision date : 2019/02/08
Version: 3.0

Page: 4/10
(30676744/SDS_GEN_CA/EN)

6. Accidental release measures

Further accidental release measures:

High risk of slipping due to leakage/spillage of product.

Personal precautions, protective equipment and emergency procedures

Use personal protective clothing.

Environmental precautions

Do not empty into drains. Do not discharge into the subsoil/soil.

Methods and material for containment and cleaning up

Spills should be contained, solidified, and placed in suitable containers for disposal.

7. Handling and Storage

Precautions for safe handling

Ensure thorough ventilation of stores and work areas. Protect against moisture.

Protection against fire and explosion:

No special precautions necessary.

Conditions for safe storage, including any incompatibilities

Segregate from foods and animal feeds. Segregate from acids. Segregate from oxidants.

Suitable materials for containers: Carbon steel (Iron), High density polyethylene (HDPE), Low density polyethylene (LDPE), Stainless steel 1.4301 (V2)

Further information on storage conditions: Containers should be stored tightly sealed in a dry place.

Storage stability:

Storage temperature: 16 - 27 °C

Protect against moisture.

The stated storage temperature is noted for health and safety in the workplace. With regard to Quality, please refer to the product specific Technical Bulletin.

8. Exposure Controls/Personal Protection

No occupational exposure limits known.

Advice on system design:

Provide local exhaust ventilation to control vapours/mists.

Personal protective equipment

Respiratory protection:

Wear a NIOSH-certified (or equivalent) organic vapour/particulate respirator as needed.

Hand protection:

Chemical resistant protective gloves

Safety Data Sheet

WALLTITE® XL RESIN

Revision date : 2019/02/08
Version: 3.0

Page: 5/10
(30676744/SDS_GEN_CA/EN)

Eye protection:

Wear face shield or tightly fitting safety goggles (chemical goggles) if splashing hazard exists.

Body protection:

Standard work clothes and shoes.

General safety and hygiene measures:

Avoid contact with skin. Handle in accordance with good industrial hygiene and safety practice. Wear protective clothing as necessary to prevent contact. Avoid inhalation of vapours/mists. Wash soiled clothing immediately.

9. Physical and Chemical Properties

Form:	liquid	
Odour:	characteristic	
Odour threshold:	No applicable information available.	
Colour:	yellowish to brown	
pH value:	≥ 7	
Freezing point:	No applicable information available.	
Boiling point:	$> 140\text{ }^{\circ}\text{C}$	
Sublimation point:	No applicable information available.	
Flash point:	$> 110\text{ }^{\circ}\text{C}$	
Flammability:	not flammable	(derived from flash point)
Lower explosion limit:	For liquids not relevant for classification and labelling. The lower explosion point may be $5 - 15\text{ }^{\circ}\text{C}$ below the flash point.	
Upper explosion limit:	For liquids not relevant for classification and labelling.	
Autoignition:	$> 250\text{ }^{\circ}\text{C}$	
Vapour pressure:	$< 0.1\text{ hPa}$ ($25\text{ }^{\circ}\text{C}$)	
Density:	approx. 1.1 g/cm^3 ($20\text{ }^{\circ}\text{C}$)	
Relative density:	No applicable information available.	
Vapour density:	No applicable information available.	
Partitioning coefficient n-octanol/water (log Pow):	not applicable	
Self-ignition temperature:	not self-igniting	
Thermal decomposition:	No decomposition if stored and handled as prescribed/indicated.	
Viscosity, dynamic:	No applicable information available.	
Viscosity, kinematic:	No applicable information available.	
Solubility in water:	partly soluble	
Solubility (quantitative):	No applicable information available.	
Solubility (qualitative):	No applicable information available.	
Evaporation rate:	Value can be approximated from Henry's Law Constant or vapor pressure.	
Other Information:	If necessary, information on other physical and chemical parameters is indicated in this section.	

Safety Data Sheet

WALLTITE® XL RESIN

Revision date : 2019/02/08
Version: 3.0

Page: 6/10
(30676744/SDS_GEN_CA/EN)

10. Stability and Reactivity

Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Corrosion to metals:

No corrosive effect on metal.

Oxidizing properties:

not fire-propagating

Chemical stability

The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions

No hazardous reactions if stored and handled as prescribed/indicated.

Conditions to avoid

Temperature: < 0 degrees Celsius

Incompatible materials

acids, oxidizing agents, isocyanates

Hazardous decomposition products

Decomposition products:

Hazardous decomposition products: carbon monoxide, carbon dioxide, nitrogen oxide, hydrogen cyanide

Thermal decomposition:

No decomposition if stored and handled as prescribed/indicated.

11. Toxicological information

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Acute Toxicity/Effects

Oral

Type of value: ATE

Value: 3,037 mg/kg

The statements are based on the properties of the individual components.

Inhalation

No applicable information available.

Dermal

No applicable information available.

Assessment other acute effects

Assessment of STOT single:

Safety Data Sheet

WALLTITE® XL RESIN

Revision date : 2019/02/08
Version: 3.0

Page: 7/10
(30676744/SDS_GEN_CA/EN)

Based on the available information there is no specific target organ toxicity to be expected after a single exposure.

Origin of data: expert judgement

Irritation / corrosion

Assessment of irritating effects: No irritation is expected under intended use and appropriate handling.

Sensitization

Assessment of sensitization: Sensitization after skin contact possible.

Aspiration Hazard

No aspiration hazard expected.

Chronic Toxicity/Effects

Repeated dose toxicity

Assessment of repeated dose toxicity: Repeated exposure may affect certain organs.

Information on: Hydroxyalkyl ether

Assessment of repeated dose toxicity: The substance may cause damage to the kidney after repeated ingestion of high doses, as shown in animal studies. The effects were only observed at doses/concentrations not relevant for classification and/or practical use conditions. These effects are not relevant to humans at occupational levels of exposure.

The substance may cause damage to the liver after repeated ingestion.

Genetic toxicity

Assessment of mutagenicity: The chemical structure does not suggest a specific alert for such an effect. No applicable information available.

Carcinogenicity

Assessment of carcinogenicity: Indication of possible carcinogenic effect in animal tests.

Information on: Bis(dialkylaminocarbomonocyclic)alkylene-carbomonocyclic, ammonium salt

Assessment of carcinogenicity: Indication of possible carcinogenic effect in animal tests. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Reproductive toxicity

Assessment of reproduction toxicity: The chemical structure does not suggest a specific alert for such an effect. No applicable information available.

Teratogenicity

Assessment of teratogenicity: The chemical structure does not suggest a specific alert for such an effect. No applicable information available.

Other Information

The product has not been tested. The statement has been derived from the properties of the individual components.

Symptoms of Exposure

The most important known symptoms and effects are described in section 2 and/or in section 11.

Safety Data Sheet

WALLTITE® XL RESIN

Revision date : 2019/02/08
Version: 3.0

Page: 8/10
(30676744/SDS_GEN_CA/EN)

Medical conditions aggravated by overexposure

Data available do not indicate that there are medical conditions that are generally recognized as being aggravated by exposure to this substance/product.

12. Ecological Information

Toxicity

Aquatic toxicity

Assessment of aquatic toxicity:

Acutely harmful for aquatic organisms. The product has not been tested. The statement has been derived from the properties of the individual components.

Toxicity to fish

Information on: Alkyl halide Phosphate

LC50 (96 h) 51 mg/l, Pimephales promelas (Fish test acute, static)

LC50 (96 h) 56 mg/l, Brachydanio rerio (Fish test acute, static)

Aquatic invertebrates

Information on: Alkyl halide Phosphate

EC50 (48 h) 131 mg/l, Daphnia magna (Daphnia test acute, static)

The statement of the toxic effect relates to the analytically determined concentration.

Aquatic plants

Information on: Alkyl halide Phosphate

EC50 (72 h) 82 mg/l (growth rate), Pseudokirchneriella subcapitata (OECD Guideline 201, static)

Nominal concentration.

Chronic toxicity to fish

Information on: Alkyl halide Phosphate

Study does not need to be conducted.

Chronic toxicity to aquatic invertebrates

Information on: Alkyl halide Phosphate

No observed effect concentration (21 d) 32 mg/l, Daphnia magna (OECD Guideline 202, part 2, semistatic)

Nominal concentration.

Microorganisms/Effect on activated sludge

Toxicity to microorganisms

Information on: Alkyl halide Phosphate

Safety Data Sheet

WALLTITE® XL RESIN

Revision date : 2019/02/08
Version: 3.0

Page: 9/10
(30676744/SDS_GEN_CA/EN)

Persistence and degradability

Assessment biodegradation and elimination (H₂O)
Poorly biodegradable.

Elimination information

Poorly biodegradable.

Bioaccumulative potential

Assessment bioaccumulation potential
Does not significantly accumulate in organisms.

Mobility in soil

Assessment transport between environmental compartments
Adsorption to solid soil phase is not expected.

Additional information

Adsorbable organically-bound halogen (AOX):
This product contains no organically-bound halogen.

Other ecotoxicological advice:
The product has not been tested. Do not discharge product into the environment without control.

13. Disposal considerations

Waste disposal of substance:

Do not discharge substance/product into sewer system. Incinerate or dispose of in a licensed facility.

Container disposal:

Do not reuse empty containers. Under no circumstances should empty drums be burned or cut open with gas or electric torch as toxic decomposition products may be liberated. Steel drums must be emptied and can be sent to a licensed drum reconditioner for reuse, a scrap metal dealer or an approved landfill. Do not attempt to refill or clean containers since residue is difficult to remove.

14. Transport Information

Land transport

TDG

Not classified as a dangerous good under transport regulations

Sea transport

IMDG

Not classified as a dangerous good under transport regulations

Air transport

IATA/ICAO

Not classified as a dangerous good under transport regulations

Safety Data Sheet

WALLTITE® XL RESIN

Revision date : 2019/02/08
Version: 3.0

Page: 10/10
(30676744/SDS_GEN_CA/EN)

15. Regulatory Information

Federal Regulations

Registration status:

Chemical DSL, CA released; restriction on use / listed

This product contains a substance subject to a Significant New Activity (SNAc) as disclosed in the Canada Gazette.

The Minister of the Environment must be notified as outlined in the SNAc prior to engaging in any new activity.

See SNAc Notice in Canada Gazette for further details.

CGII, Vol140No24p1953, CGII, Vol143No21p1974, SNAc 13957

NFPA Hazard codes:

Health: 2 Fire: 1 Reactivity: 1 Special:

16. Other Information

SDS Prepared by:

BASF NA Product Regulations

SDS Prepared on: 2019/02/08

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

WALLTITE is a registered trademark of BASF Canada or BASF SE
END OF DATA SHEET